## Distributed by:



1-800-882-1003 • 828-369-7584 Franklin, NC Visit us online www.dodgepackaging.net

ITEM NUMBER: 415996 Regency Chewing Gum Remover

(As Used On Label and List): Chewing Gum Remover

EMERGENCY MEDICAL Telephone# 1-800-228-5635 (24 Hrs)

Outside of the U.S.A. Call 651-632-9275

PRODUCT HAZARD RATINGS (HMIS®): Health = 1, Fire = 4, Reactivity = 0, Protective Equipment = B

(Rating Legend: 4 = Extreme, 3 = Serious, 2 = Moderate, 1 = Slight, 0 = Minimal)

## **SECTION I**

**SRC** 

4510 Reading Rd. TELEPHONE NUMBER FOR INFORMATION: 1-877-482-5604

Cincinnati, OH 45229 **DATE REVIEWED: 08-16-2006** NAME OF PREPARER: Ron Cepa

SECTION II - HAZARDOUS INGREDIENTS / IDENTITY INFORMATION					
Chemical Names	EXPOSURE LIMITS (LD50 ORAL RAT)	SARA Title III SEC 313	ACGIH TLV/TWA	OSHA PEL	% By Wt.
Liquified Petroleum Gas (CAS#68476-85-7)	NA	NA	1000ppm	1000ppm	100%

Unidentified ingredients are not considered hazardous under the Federal Hazard Communication Standard.

Components Listed As A Suspected Carcinogen: None

## **SECTION III - PHYSICAL CHARACTERISTICS**

Vapor Pressure (psig): 175+/- 3 @130F Boiling Point: NA Specific Gravity (H20=1): <1.0 Solubility/Water: Negligible Vapor Density (AIR=1): >1 Evaporation Rate (Ether=1): <1

Appearance and Odor: Clear, Odorless Gas

## SECTION IV - FIRE AND EXPLOSION HAZARD DATA

This product is considered to be Flammable as described in 16CFR 1500.45. Aerosol Flammability:

Flammable Limits - % Volume In Air (Propellant): LEL: 1.8 UEL: 9.2

Extinguishing Media: Carbon dioxide, foam and/or dry chemical may be used.

Containers should be cooled with water to prevent vapor pressure build up. Special Fire Fighting Procedures: Use equipment or shielding, as required, to protect personnel from bursting, rupturing or venting containers. Unusual Fire and Explosion Hazards: At elevated temperatures (over 54C-130F) containers exposed to direct

flame or heat contact should be cooled with water to prevent weakening of container structure.

# **SECTION V - REACTIVITY DATA**

Stability: Stable Hazardous Polymerization: NA

Oxygen and strong oxidizing agents Incompatibility (Materials to Avoid): Hazardous Decomposition

Products: Oxides of carbon and additional toxic chemicals may be formed in small amounts.

Do not store above 54C-130F. Keep away from heat, direct sunlight, open flames or Conditions to Avoid:

sparks. Dropping of containers may cause bursting.

## SECTION VI - HEALTH HAZARD DATA

Route(s) of Entry: Inhalation: X Eyes: X Skin: X Ingestion: X

Signs and Symptoms of Exposure: Inhalation: Simple asphyxiant. May cause dizziness, disorientation,

headaches and central nervous system depression. Liquified gas may cause freeze burns to skin and eyes. Ingestion: possible frostbite to mucous membranes and central nervous system.

Medical Conditions Generally Aggravated by Exposure: Preexisting skin or eye disorders may be aggravated by exposure to this product.

Emergency and First Aid Procedures: Inhalation: Remove from exposure, if breathing administer artifical respiration. Seek medical attention. Eye Contact: Vapor may cause mild irritation. Flush eyes with plenty of water for 15 minutes while holding eyelids open. For freeze burns seek medical attention. Skin: Flush affected area with water for 15 minutes. For freeze burns, seek medical attention. If irritation persists obtain medical attention. Ingestion: Seek medical attention.

## SECTION VII - PRECAUTIONS FOR SAFE HANDLING AND USE

Releases or Spilled: Remove all sources of ignition and ventilate area. Soak up spill with an inert absorbent and place into a designated disposal container. Consult local regulatory agency for proper disposition of material. Waste Disposal Method: Do not puncture or incinerate containers. When contents are depleted continue to depress button until all gas is expelled. Dispose of container in accordance with local, state, and federal regulations.

Handling And Storing: Avoid breathing vapor. Keep away from heat and flame. Use with adequate ventilation. Do not puncture or incinerate containers. Do not expose to direct sunlight or store at temperatures above 130F (54C). Store as Level 3 Aerosol (NFPA 30B).

Other Precautions: Please read and follow the directions on the product label; they are your best guide to using this product in the most effective way, and give the necessary safety precautions to protect your health.

## **SECTION VIII - EMPLOYEE PROTECTION**

Respiratory Protection (Type): None required if good ventilation is maintained. If exposure exceeds occupational exposure limits (Sec. II), use a NIOSH approved respirator to prevent overexposure.

Ventilation: Local exhaust is adequate under normal conditions, mechanical ventilation is optional.

Protective Gloves: Chemical resistant gloves\*.

Eye Protection: Chemical safety glasses are recommended\*.

Other Protective Clothing or Equipment: Wear impervious clothing to prevent skin contact.

Work/Hygienic Practices: Ensure strict sanitary conditions are conformed to when working around chemicals.

Protective clothing and equipment should be in accordance with 29 CFR 1910.132 and CFR 1910.133.

## **SECTION IX - OTHER REGULATORY CONTROLS**

Governmental Listings: Ingredients of this product are listed on the EPA/TSCA Inventory of Chemical Substances.

## SECTION X - TRANSPORTATION REQUIREMENTS (D.O.T. CLASSIFICATION)

Shipping Name: Consumer Commodity Hazard Class: ORM-D

NG-- Negligible NA-- Not Applicable NE-- Not Established UN-- Unavailable ND-- Not Determined While the information set forth herein is believed to be accurate as of the date hereof, the Company makes no warranty or guarantee, express or implied, and disclaims all liability arising out of the use of this information. As of: July 2, 1998