SAFETY DATA SHEET

1. Identification

Product number 1000004842

Product identifier STAINLESS STEEL POLISH & CLEANER

04-02-2015 Revision date

Company information Claire Manufacturing Co.

1005 S. Westgate Drive

Addison, IL 60101 United States

General Assistance 1-630-543-7600 Company phone

1-866-836-8855 Emergency telephone US Emergency telephone outside 1-952-852-4646

Version # 80

03-25-2015 Supersedes date Recommended use **CLEANER** None known. Recommended restrictions

2. Hazard(s) identification

Flammable aerosols Physical hazards Category 1 Health hazards Serious eye damage/eye irritation Category 2A

> Specific target organ toxicity, single exposure Category 3 narcotic effects

Aspiration hazard Category 1

Not classified. Environmental hazards Not classified. OSHA defined hazards

Label elements



Signal word

Extremely flammable aerosol. May be fatal if swallowed and enters airways. Causes serious eye Hazard statement

irritation. May cause drowsiness or dizziness.

Precautionary statement

Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Do not spray on an open Prevention

> flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Avoid breathing gas. Wash thoroughly after handling. Use only outdoors or in a well-ventilated area.

Wear eye/face protection.

If swallowed: Immediately call a poison center/doctor. If inhaled: Remove person to fresh air and Response

keep comfortable for breathing. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Call a poison center/doctor. Specific treatment (see this label). Do NOT induce vomiting. If eye irritation persists: Get medical

advice/attention.

Storage Store in a well-ventilated place. Keep container tightly closed. Store locked up. Protect from

sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

Dispose of contents/container in accordance with local/regional/national/international regulations. Disposal

Hazard(s) not otherwise

classified (HNOC)

None known.

Supplemental information None.

Composition/information on ingredients

Mixtures

Product name: STAINLESS STEEL POLISH & CLEANER

Chemical name	Common name and synonyms	CAS number	%
Distillates (Petroleum), Hydrotreated Light		64742-47-8	20 - 40
White Mineral Oil		8042-47-5	20 - 40
Acetone		67-64-1	10 - 20
Propane		74-98-6	10 - 20
Methyl Acetate		79-20-9	2.5 - 10
Fragrance		Proprietary	0.1 - 1
Odorless Mineral Spirits		64741-65-7	0.1 - 1
Vitamin E		59-02-9	0.01 - 0.1
Other components below reportable	levels		0.1 - 1

^{*}Designates that a specific chemical identity and/or percentage of composition has been withheld as a trade secret.

First-aid measures

Inhalation

Remove victim to fresh air and keep at rest in a position comfortable for breathing. Oxygen or artificial respiration if needed. Do not use mouth-to-mouth method if victim inhaled the substance. Induce artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device. Call a POISON CENTER or doctor/physician.

Skin contact

Wash off with soap and water. Get medical attention if irritation develops and persists.

Eve contact

Rinse with water. Get medical attention if irritation develops and persists.

Ingestion

Rinse mouth. Get medical attention if symptoms occur.

Most important

symptoms/effects, acute and

delayed

May cause drowsiness and dizziness. Headache. Nausea, vomiting. Aspiration may cause pulmonary edema and pneumonitis. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision.

Indication of immediate medical attention and special

treatment needed

Provide general supportive measures and treat symptomatically. Keep victim warm. Keep victim under observation. Symptoms may be delayed.

General information

Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Show this safety data sheet to the doctor in attendance.

Fire-fighting measures

Suitable extinguishing media

Unsuitable extinguishing

media

Powder. Alcohol resistant foam. Dry chemicals. Carbon dioxide (CO2). Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from

the chemical

Special protective equipment and precautions for firefighters

Fire-fighting

Specific methods

equipment/instructions

Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.

Contents under pressure. Pressurized container may explode when exposed to heat or flame.

Move containers from fire area if you can do so without risk. Cool containers exposed to heat with water spray and remove container, if no risk is involved. Containers should be cooled with water to prevent vapor pressure build up. For massive fire in cargo area, use unmanned hose holder or monitor nozzles, if possible. If not, withdraw and let fire burn out.

Use standard firefighting procedures and consider the hazards of other involved materials. Move

containers from fire area if you can do so without risk. In the event of fire and/or explosion do not breathe fumes. General fire hazards Extremely flammable aerosol.

Accidental release measures

Personal precautions. protective equipment and emergency procedures

Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Keep out of low areas. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Wear appropriate protective equipment and clothing during clean-up. Avoid breathing gas. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Methods and materials for containment and cleaning up

Refer to attached safety data sheets and/or instructions for use. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. Stop leak if you can do so without risk. Move the cylinder to a safe and open area if the leak is irreparable. Use water spray to reduce vapors or divert vapor cloud drift. Isolate area until gas has dispersed. Prevent entry into waterways, sewer, basements or confined areas. Following product recovery, flush area with water. For waste disposal, see section 13 of the SDS.

Environmental precautions

Avoid release to the environment. Inform appropriate managerial or supervisory personnel of all environmental releases. Prevent further leakage or spillage if safe to do so. Avoid discharge into drains, water courses or onto the ground.

7. Handling and storage

Precautions for safe handling

Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. All equipment used when handling the product must be grounded. Do not re-use empty containers. Avoid breathing gas. Avoid contact with eyes. Avoid prolonged or repeated contact with skin. Avoid prolonged exposure. Use only outdoors or in a well-ventilated area. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Avoid release to the environment. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities

Level 3 Aerosol.

Store locked up. Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50 °C/122 °F. Do not puncture, incinerate or crush. Do not handle or store near an open flame, heat or other sources of ignition. This material can accumulate static charge which may cause spark and become an ignition source. Store in a well-ventilated place. Refrigeration recommended. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure controls/personal protection

Occupational exposure limits

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) Components Value Type Acetone (CAS 67-64-1) **PEL** 2400 mg/m3 1000 ppm Methyl Acetate (CAS PEL 610 mg/m3 79-20-9) 200 ppm Propane (CAS 74-98-6) **PEL** 1800 mg/m3 1000 ppm US. ACGIH Threshold Limit Values Components Type Value STEL 750 ppm Acetone (CAS 67-64-1) TWA 500 ppm Methyl Acetate (CAS **STEL** 250 ppm 79-20-9) TWA 200 ppm US. NIOSH: Pocket Guide to Chemical Hazards Components Value Type Acetone (CAS 67-64-1) **TWA** 590 mg/m3 250 ppm **STEL** 760 mg/m3 Methyl Acetate (CAS 79-20-9) 250 ppm **TWA** 610 mg/m3 200 ppm **TWA** 1800 mg/m3 Propane (CAS 74-98-6) 1000 ppm

Product name: STAINLESS STEEL POLISH & CLEANER

SDS US 3 / 10 Biological limit values

ACGIH Biological Exposure Indices

Components Value Determinant Specimen Sampling Time Acetone

* - For sampling details, please see the source document.

50 mg/l

Appropriate engineering

Acetone (CAS 67-64-1)

controls

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Provide eyewash station.

Urine

Individual protection measures, such as personal protective equipment

Eye/face protection Wear safety glasses with side shields (or goggles).

Wear appropriate chemical resistant gloves. Hand protection

Skin protection

Other Wear appropriate chemical resistant clothing.

If permissible levels are exceeded use NIOSH mechanical filter / organic vapor cartridge or an Respiratory protection

air-supplied respirator.

Wear appropriate thermal protective clothing, when necessary. Thermal hazards

General hygiene When using do not smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work considerations

clothing and protective equipment to remove contaminants.

Physical and chemical properties

Clear. **Appearance**

> Gas. Form Physical state

> > Aerosol.

Not available.

Color Light yellow.

Citrus Odor

Not available. Odor threshold Not available. Ηα

Initial boiling point and boiling

Melting point/freezing point

range

38.25 °F (3.47 °C) estimated

Flash point -156.0 °F (-104.4 °C) Propellant estimated

Not available. Evaporation rate Not available. Flammability (solid, gas) Upper/lower flammability or explosive limits

Flammability limit - lower

2.5 % estimated

(%)

Flammability limit - upper

12 % estimated

Not available. Explosive limit - lower (%) Not available. Explosive limit - upper (%)

45 - 65 psig @70F estimated Vapor pressure

Not available. Vapor density Not available. Relative density

Solubility(ies)

Solubility (water) Not available. Partition coefficient Not available.

(n-octanol/water)

505.58 °F (263.1 °C) estimated Auto-ignition temperature

Decomposition temperature Not available. Not available. Viscosity

Other information

Specific gravity 0.765 - 0.865 estimated

Stability and reactivity

Reactivity The product is stable and non-reactive under normal conditions of use, storage and transport.

Material is stable under normal conditions. Chemical stability Possibility of hazardous Hazardous polymerization does not occur.

reactions

Conditions to avoid Avoid temperatures exceeding the flash point. Contact with incompatible materials.

Acids. Strong oxidizing agents. Nitrates. Incompatible materials

Hazardous decomposition

products

No hazardous decomposition products are known.

Toxicological information

Information on likely routes of exposure

Droplets of the product aspirated into the lungs through ingestion or vomiting may cause a serious Ingestion

chemical pneumonia.

Inhalation Toxic if inhaled. May cause drowsiness and dizziness. Headache. Nausea, vomiting. Narcotic

effects.

Skin contact No adverse effects due to skin contact are expected.

Eve contact Causes serious eye irritation.

Symptoms related to the physical, chemical and toxicological characteristics May cause drowsiness and dizziness. Headache. Nausea, vomiting. Aspiration may cause pulmonary edema and pneumonitis. Severe eye irritation. Symptoms may include stinging,

tearing, redness, swelling, and blurred vision.

Information on toxicological effects

May be fatal if swallowed and enters airways. Toxic if inhaled. Narcotic effects. Acute toxicity

Test Results Components **Species**

Acetone (CAS 67-64-1)

Acute Dermal

LD50 Guinea pig > 7426 mg/kg, 24 Hours

> 9.4 ml/kg, 24 Hours

Rabbit > 7426 mg/kg, 24 Hours

> 9.4 ml/kg, 24 Hours

20 mg/kg

Inhalation

LC50 Rat 55700 ppm, 3 Hours 132 mg/l, 3 Hours

50.1 mg/l

Oral

LD50 Mouse 3000 mg/kg

> Rabbit 5340 mg/kg Rat 5800 mg/kg

> > 2.2 ml/kg

Other

LD50 Mouse 1297 mg/kg

> Rat 5500 mg/kg

Distillates (Petroleum), Hydrotreated Light (CAS 64742-47-8)

Acute

Dermal

LD50 Rabbit > 2000 mg/kg

> 2000 mg/kg, 24 Hours

Product name: STAINLESS STEEL POLISH & CLEANER

SDS US

Components	Species	Test Results
Inhalation		
LC50	Rat	> 7.5 mg/l, 6 Hours
		> 4.6 mg/l, 4 Hours
Oral		
LD50	Rat	> 5000 mg/kg
Methyl Acetate (CAS 79-20-9)		
Acute		
Dermal		
LD50	Rat	> 2000 mg/kg, 24 Hours
Inhalation		
LC100	Rabbit	98.4 mg/l, 4 Hours
Oral		
LD50	Rat	6482 mg/kg
Propane (CAS 74-98-6)		
Acute		
Inhalation		
LC50	Mouse	1237 mg/l, 120 Minutes
		52 %, 120 Minutes
	Rat	1355 mg/l
		658 mg/l/4h
White Mineral Oil (CAS 8042-4	47-5)	
Acute	,	
Dermal		
LD50	Rabbit	> 2000 mg/kg, 24 Hours
Inhalation		
LC50	Rat	2.18 mg/l, 4 Hours
Oral		
LD50	Rat	5000.0001 mg/kg

Skin corrosion/irritation Prolonged skin contact may cause temporary irritation.

Serious eye damage/eye

irritation

Respiratory or skin sensitization

Respiratory sensitization Not available.

Skin sensitization This product is not expected to cause skin sensitization.

Causes serious eye irritation.

No data available to indicate product or any components present at greater than 0.1% are Germ cell mutagenicity

mutagenic or genotoxic.

This product is not considered to be a carcinogen by IARC, ACGIH, NTP, or OSHA. Carcinogenicity

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed.

Reproductive toxicity This product is not expected to cause reproductive or developmental effects.

Specific target organ toxicity -

single exposure

May cause drowsiness and dizziness.

Specific target organ toxicity -

repeated exposure

Not classified.

Aspiration hazard May be fatal if swallowed and enters airways.

Chronic effects Prolonged inhalation may be harmful.

12. Ecological information

Ecotoxicity Harmful to aquatic life with long lasting effects.

Product name: STAINLESS STEEL POLISH & CLEANER

Components Species Test Results

Acetone (CAS 67-64-1)

Aquatic

Crustacea EC50 Water flea (Daphnia magna) 21.6 - 23.9 mg/l, 48 hours
Fish LC50 Rainbow trout,donaldson trout 4740 - 6330 mg/l, 96 hours

(Oncorhynchus mykiss)

Distillates (Petroleum), Hydrotreated Light (CAS 64742-47-8)

Aquatic

Fish LC50 Rainbow trout, donaldson trout 2.9 mg/l, 96 hours

(Oncorhynchus mykiss)

Methyl Acetate (CAS 79-20-9)

Aquatic

 Algae
 IC50
 Algae
 120.0001 mg/L, 72 Hours

 Crustacea
 EC50
 Daphnia
 1026.7 mg/L, 48 Hours

 Fish
 LC50
 Fathead minnow (Pimephales promelas)
 295 - 348 mg/l, 96 hours

Odorless Mineral Spirits (CAS 64741-65-7)

Aquatic

Algae IC50 Algae 30000 mg/L, 72 Hours

White Mineral Oil (CAS 8042-47-5)

Aquatic

Fish LC50 Fish 10000.0001, 96 Hours

Persistence and degradability No data is available on the degradability of this product.

Bioaccumulative potential No data available.

Partition coefficient n-octanol / water (log Kow)

Acetone -0.24
Methyl Acetate 0.18
Propane 2.36

Mobility in soil No data available.

Other adverse effects No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation

potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

Disposal instructions Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Contents

under pressure. Do not puncture, incinerate or crush. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose of contents/container in accordance with local/regional/national/international

regulations.

Local disposal regulations Dispose in accordance with all applicable regulations.

Hazardous waste code

The waste code should be assigned in discussion between the user, the producer and the waste

disposal company.

US RCRA Hazardous Waste U List: Reference

Acetone (CAS 67-64-1) U002

Waste from residues / unused

products

Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see:

Disposal instructions).

Contaminated packaging Empty containers should be taken to an approved waste handling site for recycling or disposal.

Since emptied containers may retain product residue, follow label warnings even after container is

emptied. Do not re-use empty containers.

14. Transport information

DOT

UN number UN1950

UN proper shipping name Aerosols, flammable

^{*} Estimates for product may be based on additional component data not shown.

Transport hazard class(es)

Class 2.1 Subsidiary risk Label(s) 2.1

Packing group Not applicable.

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

Special provisions Packaging exceptions 306 Packaging non bulk None None Packaging bulk

This product meets the exception requirements of section 173.306 as a limited quantity and may be shipped as a limited quantity. Until 12/31/2020, the "Consumer Commodity - ORM-D" marking may still be used in place of the new limited quantity diamond mark for packages of UN 1950 Aerosols. Limited quantities require the limited quantity diamond mark on cartons after 12/31/20 and may be used now in place of the "Consumer Commodity ORM-D" marking and both may be displayed concurrently.

IATA

UN1950 **UN** number

UN proper shipping name Aerosols, flammable

Transport hazard class(es)

2.1 Class Subsidiary risk 2.1 Label(s) Packing

Not applicable. group Environmental

hazards ERG Code No. 10L

Special precautions for user

Read safety instructions, SDS and emergency procedures before handling.

Other information

Passenger and cargo

aircraft

Allowed. Allowed.

Cargo aircraft only Packaging Exceptions LTD QTY

IMDG

UN number UN1950 UN proper shipping name **AEROSOLS**

Transport hazard class(es)

Class 2.1 Subsidiary risk Label(s) Packing 2.1

Not applicable. group Environmental

hazards

Marine pollutant No. F-D, S-U EmS

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

Packaging Exceptions LTD QTY Transport in bulk according to Not applicable.

Annex II of MARPOL 73/78 and

the IBC Code

DOT



Product name: STAINLESS STEEL POLISH & CLEANER

Product #: 1000004842 Version #: 08 Revision date: 04-02-2015 Issue date: 12-30-2014



Regulatory information

US federal regulations

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication

Standard, 29 CFR 1910.1200.

All components are on the U.S. EPA TSCA Inventory List.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

Acetone (CAS 67-64-1)

Listed.

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Immediate Hazard - Yes Hazard categories

> Delayed Hazard - No Fire Hazard - Yes Pressure Hazard - Yes Reactivity Hazard - No

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous

No

chemical

SARA 313 (TRI reporting)

Chemical name	CAS number	% by wt.
Methanol	67-56-1	0.1 - 1
Acetaldehyde	75-07-0	0.01 - 0.1

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Propane (CAS 74-98-6)

Safe Drinking Water Act Not regulated.

(SDWA)

Drug Enforcement Administration (DEA). List 2, Essential Chemicals (21 CFR 1310.02(b) and 1310.04(f)(2) and

Chemical Code Number

Acetone (CAS 67-64-1) 6532

Drug Enforcement Administration (DEA). List 1 & 2 Exempt Chemical Mixtures (21 CFR 1310.12(c))

Acetone (CAS 67-64-1) 35 %WV

DEA Exempt Chemical Mixtures Code Number

Acetone (CAS 67-64-1) 6532

US state regulations

US. Massachusetts RTK - Substance List

Acetone (CAS 67-64-1) Methyl Acetate (CAS 79-20-9) Propane (CAS 74-98-6)

Product name: STAINLESS STEEL POLISH & CLEANER

US. New Jersey Worker and Community Right-to-Know Act

Acetone (CAS 67-64-1) Methyl Acetate (CAS 79-20-9) Propane (CAS 74-98-6)

US. Pennsylvania Worker and Community Right-to-Know Law

Acetone (CAS 67-64-1) Methyl Acetate (CAS 79-20-9) Propane (CAS 74-98-6)

US. Rhode Island RTK

Acetone (CAS 67-64-1) Propane (CAS 74-98-6)

US. California Proposition 65

WARNING: This product contains a chemical known to the State of California to cause cancer and birth defects or other reproductive harm.

US - California Proposition 65 - CRT: Listed date/Carcinogenic substance Acetaldehyde (CAS 75-07-0) Listed: April 1, 1988 US - California Proposition 65 - CRT: Listed date/Developmental toxin

Methanol (CAS 67-56-1) Listed: March 16, 2012

International Inventories

Country(s) or region On inventory (yes/no)* Inventory name Australia Australian Inventory of Chemical Substances (AICS) Yes Canada Domestic Substances List (DSL) Yes Canada Non-Domestic Substances List (NDSL) No China Inventory of Existing Chemical Substances in China (IECSC) Yes European Inventory of Existing Commercial Chemical Europe Yes

Substances (EINECS)

European List of Notified Chemical Substances (ELINCS) No Europe Japan Inventory of Existing and New Chemical Substances (ENCS) Yes Existing Chemicals List (ECL) No Korea New Zealand New Zealand Inventory No **Philippines** Philippine Inventory of Chemicals and Chemical Substances No

(PICCS)

United States & Puerto Rico Toxic Substances Control Act (TSCA) Inventory Yes

16. Other information, including date of preparation or last revision

12-30-2014 Issue date 04-02-2015 Revision date

Version # 80

The information provided in this Safety Data Sheet is correct to the best of our knowledge, Disclaimer

> information and belief at the date of its publication. The information given is designed only as a quidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other

materials or in any process, unless specified in the text.

Product and Company Identification: Alternate Trade Names **Revision Information**

Product name: STAINLESS STEEL POLISH & CLEANER

^{*}A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s) A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).