Safety Data Sheet



according to OSHA Hazard Communication 29 CFR Part 1910.1200

according to Regulation (EC) No. 1907/2006 Article 31

Section 1. Identification

Product Code: 999822Y

Product Name: DURASET 2 98:2 TRK PROF YELLOW

Product Type: MMA

Recommended Use: Traffic Markings

Supplied by: Ennis-Flint

A Traffic Safety Solutions Company

115 Todd Court

Thomasville, NC 27360

T: 800.331.8118 (For Technical Inquiries)

Emergency Telephone: Chemtrec 1-800-424-9300

Section 2. Hazard(s) identification

EMERGENCY OVERVIEW: FLAMMABLE liquid and vapor. This product contains a component suspected of causing cancer. However, it is in a non-respirable form and inhalation is unlike to occur from exposure. This classification is relevant when exposed to dust or powder form only (e.g. sanding, grinding).

Classification

Symbol(s) of Product





Signal Word

Danger

GHS Named Chemicals On Label

Titanium Dioxide, Crystalline Silica, Quartz

GHS HAZARD STATEMENTS

Flammable Liquid, category 2 H225 Highly flammable liquid and vapour. Carcinogenicity, category 2 H351 Suspected of causing cancer.

STOT, repeated exposure, category 1 H372 Causes damage to organs through prolonged or repeated exposure.

GHS PRECAUTIONARY STATEMENTS

P201 Obtain special instructions before use.

P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

P233 Keep container tightly closed.

P240 Ground/bond container and receiving equipment.

P241 Use explosion-proof electrical/ventilating/lighting/.../ equipment.

P242 Use only non-sparking tools.

P243 Take precautionary measures against static discharge.
P260 Do not breathe dust/fume/gas/mist/vapours/spray.
P270 Do no eat, drink or smoke when using this product.
P281 Use personal protective equipment as required.
P308+P313 IF exposed or concerned: Get medical advice/attention.
P314 Get medical advice/attention if you feel unwell.

Section 3. Composition/Information on ingredients

| Chemical Name | <u>CAS-No.</u> | <u>Wt. %</u> | GHS Symbols | GHS Statements |
|----------------------------|----------------|--------------|-------------|----------------|
| Crystalline Silica, Quartz | 14808-60-7 | 10-25 | GHS08 | H351-372 |
| Titanium Dioxide | 13463-67-7 | 2.5-10 | GHS08 | H351 |

| Chemical Name | CAS-No. | EINECS No. | REACH Reg No. | M-Factors |
|----------------------------|------------|------------|---------------|-----------|
| Crystalline Silica, Quartz | 14808-60-7 | 238-878-4 | not available | 0 |
| Titanium Dioxide | 13463-67-7 | 236-675-5 | not available | 0 |

The text for GHS Hazard Statements shown above (if any) is given in the "Other information" Section.

Section 4. First-aid measures



FIRST AID - INHALATION: Move to fresh air. Consult a physician if symptoms persist.

FIRST AID - SKIN CONTACT: Wash affected area immediately with soap and plenty of water. Remove contaminated clothing and launder before reuse. Consult a physician if symptoms persist.

FIRST AID - EYE CONTACT: Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Consult a physician if symptoms persist.

FIRST AID - INGESTION: Do NOT induce vomiting. If conscious, rinse mouth and drink plenty of water. Never give anything by mouth to an unconscious person. Consult a physician.

Section 5. Fire-fighting measures

UNUSUAL FIRE AND EXPLOSION HAZARDS: Flammable liquid. Vapors can form an ignitable mixture with air. Vapors can flow along surfaces to a distant ignition source and flash back. Vapors can spread along ground and collect in low or confined areas (sewers, basements, tanks). Water spray may reduce vapor, buy may not prevent ignition in closed spaces.

SPECIAL FIREFIGHTING PROCEDURES: Flammable. Cool fire-exposed containers using water spray. As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

EXTINGUISHING MEDIA: Alcohol Foam, Carbon Dioxide, Dry Chemical, Foam, Water Fog

Section 6. Accidental release measures

ENVIRONMENTAL PRECAUTIONS: Avoid release to the environment. For larger spills, cover drains and build dikes to prevent entry into sewer systems or bodies of water.

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Take precautionary measures against static discharges. All equipment used when handling the product must be grounded. Use personal protective equipment. Ensure adequate ventilation. Dike far ahead of liquid spill for later disposal. Soak up with inert absorbent material. Take up mechanically. Keep in suitable and closed containers for disposal. Use clean non-sparking tools to collect absorbed material.

Section 7. Handling and storage





HANDLING: Flammable liquid. Avoid heat, sparks and open flames. Ensure adequate ventilation. Avoid breathing vapor, mists or dust. Avoid contact with eyes, skin, and clothing. Wear appropriate personal protective equipment. Wash contaminated clothing before reuse. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Observe good industrial hygiene practices. Take precautionary measures against static discharges. All equipment used when handling the product must be grounded.

STORAGE: Keep containers tightly closed in a cool, well-ventilated place. Keep in properly labeled containers.

Section 8. Exposure controls/personal protection

Ingredients with Occupational Exposure Limits

<u>Chemical Name</u> <u>ACGIH TLV-TWA</u> <u>ACGIH-TLV STEL</u> <u>OSHA PEL-TWA</u> <u>OSHA PEL-CEILING</u>

Crystalline Silica, Quartz 0.025 mg/m3 0.05 mg/m3
Titanium Dioxide 10 mg/m3 15 mg/m3

Name Percentage VME mg/m3 VME ppm OEL Nota

Titanium Dioxide 2.5-10 10 0 15 mg/m3

Further Advice: MEL = Maximum Exposure Limit OES = Occupational Exposure Standard SUP = Supplier's Recommendation Sk = Skin Sensitizer N.E. = Not Established

Personal Protection



RESPIRATORY PROTECTION: If exposure limits are exceeded or irritation is experienced, NIOSH/MSHA approved respiratory protection should be worn. Positive-pressure supplied air respirators may be required for high airborne contaminant concentrations. Respiratory protection must be provided in accordance with current local regulations.



SKIN PROTECTION: Protective gloves/clothing.



EYE PROTECTION: Safety glasses with side-shields.



OTHER PROTECTIVE EQUIPMENT: Eyewash stations, safety showers, ventilation systems.



HYGIENIC PRACTICES: When using, do not eat, drink or smoke. Provide regular cleaning of equipment, work area and clothing. Wash hands before breaks and immediately after handling the product. Handle in accordance with good industrial hygiene and safety practice.

Section 9. Physical and chemical properties

Appearance: yellow Physical State: Liquid

Odor: Acrid, Fruity Odor Threshold: Not Established

Density, g/cm3:1.793pH:NIFreeze Point, °C:NIViscosity:NISolubility in Water:Not solublePartition Coefficient, n-octanol/NI

Decompostion Temp., °C: NI water:

Boiling Point, °C: **Explosive Limits, vol%:** N.I. N.I. Combustibility: Supports Combustion Flash Point, °C: 13 **Evaporation Rate:** Auto-ignition Temp., °C: Slower than Diethyl Ether NI Vapor Density: Heavier than air Vapor Pressure: NΙ

(See "Other information" Section for abbreviation legend)

Section 10. Stability and reactivity

STABILITY: Stable under recommended storage conditions.

CONDITIONS TO AVOID: Excessive heat.

INCOMPATIBILITY: Oxidizing agentsFree-radical generating sources

HAZARDOUS DECOMPOSITION PRODUCTS: Carbon monoxide. Carbon dioxide.

HAZARDOUS POLYMERIZATION: Polymerization may occur when exposed to excessive heating and incompatibles.

Section 11. Toxicological information



Practical Experiences

EFFECT OF OVEREXPOSURE - INHALATION: Irritating to the respiratory tract (nose, mouth, mucous membranes)

EFFECT OF OVEREXPOSURE - SKIN CONTACT: Irritating to skin.

EFFECT OF OVEREXPOSURE - EYE CONTACT: Direct eye contact may cause irritation.

EFFECT OF OVEREXPOSURE - INGESTION: Ingestion may cause irritation to mucous membranes. May cause gastrointestinal irritation, nausea, vomiting, and diarrhea.

EFFECT OF OVEREXPOSURE - CHRONIC HAZARDS: This product contains titanium dioxide in a non-respirable form. Inhalation of titanium dioxide is unlikely to occur from exposure to this product. Inhalation exposure to respirable levels of crystalline silica may cause respiratory impairment and lung damage. This product contains crystalline silica (quartz) in a non-respirable form. Inhalation of crystalline silica is unlikely to occur from exposure to this product. Crystalline silica (quartz) has been classified by the International Agency for Research on Cancer (IARC) as a known human carcinogen.

Acute Toxicity Values

The acute effects of this product have not been tested. Data on individual components are tabulated below:

| CAS-No. | Name according to EEC | Oral LD50 | Dermal LD50 | Gas LC50 |
|------------|----------------------------|-------------------|----------------------|------------|
| 14808-60-7 | Crystalline Silica, Quartz | >2000 mg/kg | > 2000 mg/kg | >20001 ppm |
| 13463-67-7 | Titanium Dioxide | > 10000 mg/kg rat | > 10000 mg/kg rabbit | >20001 ppm |

N.I. - No Information

Section 12. Ecological information

ECOLOGICAL INFORMATION: The environmental impact of this product has not been fully investigated.

Further Ecological Information

Contains the following ingredients which are classified as water dangerous according to EEC directive No. 76/464/EEC in percentages > 1%.

| CAS-No. | Name according to EEC | Bio. Conc. Factor (BCF) | Octanol-water par. Coeff (KOW) |
|------------|----------------------------|-------------------------|--------------------------------|
| 14808-60-7 | Crystalline Silica, Quartz | not available | not available |
| 13463-67-7 | Titanium Dioxide | not available | not available |

Section 13. Disposal considerations



Product

DISPOSAL METHOD: This material, as supplied, is a hazardous waste according to federal regulations (40 CFR 261). Dispose of contents/ container in accordance with the local/regional/national/international regulations. Do not re-use empty containers. Empty containers pose a potential fire and explosion hazard. Do not cut, puncture of weld containers.

European Waste Code: 080111 waste paint/var.w.org.solv/DS

Uncleaned Packaging

European Waste Code: 150110 packaging dangerous residuals

Section 14. Transport information

SPECIAL TRANSPORT PRECAUTIONS: No Information

Road Transport

 UN Number:
 UN1263

 ADR/RID Class:
 3

 Packing Group:
 II

 Shipping Name:
 Paint

Primary Shipping Hazard: No Information

Road Tunnel Transport Code:

Sea Transport

UN Number:

IMDG/GGVSee Class:

EmS-No:

Packing Group:

Shipping Name:

UN1263

3

F-E, S-E

II

Paint

Primary Shipping Hazard:

No Information

Marine Pollutant: Not A Marine Pollutant

Shipping Hazard(Marine Pollutant):

No Information

Air Transport

UN Number: UN1263
ICAO/IATA Class: 3
Packing Group: II
Shipping Name: Paint

Primary Shipping Hazard:

No Information

Section 15. Regulatory information

U.S. Federal Regulations:

CERCLA - SARA Hazard Category

This product has been reviewed according to the EPA 'Hazard Categories' promulgated under Sections 311 and 312 of the Superfund Amendment and Reauthorization Act of 1986 (SARA Title III) and is considered, under applicable definitions, to meet the following categories:

Flammable (gases, aerosols, liquids, or solids), Carcinogenicity, Specific target organ toxicity (single or repeated exposure)

SARA SECTION 313:

This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendment and Reauthorization Act of 1986 and 40 CFR part 372:

Chemical NameCAS-No.Dinonylphenol (branched)872-50-4

TOXIC SUBSTANCES CONTROL ACT:

This product contains the following chemical substances subject to the reporting requirements of TSCA 12(B) if exported from the United States:

Chemical NameCAS-No.Crystalline Silica, Quartz14808-60-7Titanium Dioxide13463-67-7Dinonylphenol (branched)872-50-4Silicon dioxide, amorphous7631-86-9Lithium Chloride7447-41-8

U.S. State Regulations:

NEW JERSEY RIGHT-TO-KNOW:

The following materials are non-hazardous, but are among the top five components in this product.

Chemical NameCAS-No.Silicon Dioxide99439-28-8

No Chemical Name Found

Calcium Carbonate 1317-65-3

PENNSYLVANIA RIGHT-TO-KNOW

The following non-hazardous ingredients are present in the product at greater than 3%.

Chemical NameCAS-No.Silicon Dioxide99439-28-8

No Chemical Name Found

Calcium Carbonate 1317-65-3

CALIFORNIA PROPOSITION 65 CARCINOGENS

Warning: The following ingredients present in the product are known to the state of California to cause Cancer:

Chemical NameCAS-No.Crystalline Silica, Quartz14808-60-7Titanium Dioxide13463-67-7

CALIFORNIA PROPOSITION 65 REPRODUCTIVE TOXINS

Warning: The following ingredients present in the product are known to the state of California to cause birth defects, or other reproductive hazards.

No Proposition 65 Reproductive Toxins exist in this product.

International Regulations: As follows -

CANADIAN WHMIS:

This SDS has been prepared in compliance with Controlled Product Regulations except for the use of the 16 headings.

WHMIS Class: B2, D2A, D2B

Denmark

B-Value: 0.000000

France

Storage Conditions: No Information

Professional Illness Table:

<u>CAS Number</u> <u>Chemical Name</u> <u>Professional Illness</u>

14808-60-7Crystalline Silica, Quartznot available13463-67-7Titanium Dioxidenot available

Germany

VbF-Class: No Information

WGK-class: 3

Remarks: WGK 0 = in general not a water pollutant

WGK 1 = weak water pollutant WGK 2 = water pollutant

WGK 3 = severe water pollutant

Processing restrictions:*

Incident Regulation:

No Information

Spain

Storage Conditions: No Information

Switzerland

VOC-Value: 0.22

United Kingdom

Storage Conditions: No Information

Section 16. Other information, including date of preparation of the last revision

Revision Date: 8/21/2018 Supercedes Date: 8/21/2018

Reason for revision: Substance and/or Product Properties Changed in Section(s):

01 - Product Information

Datasheet produced by: Regulatory Department

HMIS Ratings:

| | 9 | | | | | | |
|---------------|----|---------------|---|-------------|---|----------------------|------|
| Health: | *2 | Flammability: | 3 | Reactivity: | 2 | Personal Protection: | X |
| NFPA Ratings: | | | | | | | |
| Health: | 2 | Flammability: | 3 | Reactivity: | 2 | Hazards: | N.I. |

Volatile Organic Compounds, gr/ltr:

Text for GHS Hazard Statements shown in Section 3 describing each ingredient:

H351 Suspected of causing cancer.

H372 Causes damage to organs through prolonged or repeated exposure.

Icons for GHS Pictograms shown in Section 3 describing each ingredient:

GHS08



Legend: N.A. - Not Applicable, N.E. - Not Established, N.D. - Not Determined, N.I. - No Information

The information on this sheet corresponds to our present knowledge. It is not a specification and it does not guarantee specific properties. The information is intended to provide general guidance as to health and safety based upon our knowledge of the handling, storage, and use of the product. It is not applicable to unusual or non-standard uses of the product where instructions and recommendations are not followed. Any use of the product not in conformance with this SDS or in combination with any other product or process is the responsibility of the user.