Revision Date: 08/23/2006 000000015369/Version: 2.0 Print Date: 10/03/2006

Page: 1/6



1. Identification of the substance/preparation and of the company/undertaking

Product name: KODAK Brown Toner

Product code: 1464452

Supplier: EASTMAN KODAK COMPANY, 343 State Street, Rochester, New York, 14650

For Emergency Health, Safety & Environmental Information, call (585) 722-5151 (USA)

For other information or to request an MSDS, call (800) 242-2424.

Synonyms: PCD 6591

Product Use: Toner

2. Hazards identification

CONTAINS: Potassium polysulfides (37199-66-9)

DANGER!

CONTACT WITH ACID LIBERATES FLAMMABLE AND POISONOUS GAS CAUSES SKIN AND EYE BURNS DUST, MIST OR VAPOUR IRRITATING TO THE EYES AND RESPIRATORY TRACT HARMFUL IF INHALED, ABSORBED THROUGH SKIN, OR SWALLOWED

NFPA Hazard Ratings: Health - 3, Flammability - 1, Instability - 0

NOTE: NFPA 704 (2001) hazard indexes involves data review and interpretation that may vary among companies. It is intended only for rapid, general identification of the magnitude of the potential hazards. To adequately address safe handling, ALL information in this MSDS must be considered.

3. Composition/information on ingredients

Weight %	Components (CAS-No.)
70 - 75	Water (7732-18-5)
20 - 25	Potassium polysulfides (37199-66-9)
5 - 10	Sodium carbonate (497-19-8)

4. First aid measures

Inhalation: If inhaled, move to fresh air. Get medical attention.

Eyes: In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. Get medical attention immediately.

Revision Date: 08/23/2006 000000015369/Version: 2.0 Print Date: 10/03/2006

Page: 2/6

Skin: In case of contact, immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes. Get medical attention if symptoms occur. Wash contaminated clothing before re-use. Destroy or thoroughly clean contaminated shoes.

Ingestion: If swallowed, DO NOT induce vomiting. Never give anything by mouth to an unconscious person. Call a physician or poison control center immediately.

Notes to physician:

Treatment: Strong alkalis bind tissue protein. Following initial flushing of the eye with water, continued irrigation of the eye with saline is recommended. Treatment should be continued until pH of tears reaches neutral.

5. Fire-fighting measures

Extinguishing Media: Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide.

Special Fire-Fighting Procedures: Wear self-contained breathing apparatus and protective suit. Fire or excessive heat may produce hazardous decomposition products.

Hazardous Combustion Products: Carbon oxides, sulphur oxides, (see also Hazardous Decomposition Products section).

Unusual Fire and Explosion Hazards: None.

6. Accidental release measures

Methods for cleaning up: Absorb spill with vermiculite or other inert material, then place in a container for chemical waste. Clean surface thoroughly to remove residual contamination.

7. Handling and storage

Personal precautions: Do not breathe vapours or spray mist. Keep container tightly closed. Do not get in eyes and avoid contact with skin and clothing. Use only with adequate ventilation. Wash thoroughly after handling.

Prevention of Fire and Explosion: Keep from contact with oxidizing materials.

Storage: Keep container tightly closed. Keep away from incompatible substances (see Incompatibility section.)

8. Exposure controls / personal protection

Occupational exposure controls: Not established

Ventilation: Use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels to an acceptable level.

Respiratory protection: If engineering controls do not maintain airborne concentrations to an acceptable level, an approved respirator must be worn. Respirator type: N95 Particulate Filter. A full-face

Revision Date: 08/23/2006 000000015369/Version: 2.0 Print Date: 10/03/2006

Page: 3/6

positive-pressure air-supplied respirator must be worn if hazardous decomposition products are likely to be released or have been released. See Stability and Reactivity Section. If respirators are used, a program should be instituted to assure compliance with applicable federal, state, commonwealth, provincial, or local laws and regulations.

Eye protection: Wear safety glasses with side shields (or goggles) and a face shield.

Skin and body protection: Wear impervious gloves and protective clothing appropriate for the risk of

exposure.

Recommended Decontamination Facilities: Safety shower, eye wash, washing facilities as appropriate to condition of use.

9. Physical and Chemical Properties

Physical form: liquid

Colour: amber

Odour: sulphurous

Specific gravity: 1.24

Vapour pressure: 24 mbar (18.0 mm Hg)

Vapour density: 0.6

Volatile fraction by weight: 70 - 75 %

Boiling point/range: > 100.0 °C (> 212.0 °F)

Water solubility: complete

pH: 12.9

Flash point: does not flash

10. Stability and reactivity

Stability: Stable under normal conditions.

Incompatibility: Acids, Strong oxidizing agents. Contact with acid liberates flammable and poisonous

gas.

Hazardous decomposition products: sulphur oxides, hydrogen sulphide.

Hazardous Polymerization: Hazardous polymerization does not occur.

11. Toxicological information

Revision Date: 08/23/2006 000000015369/Version: 2.0 Print Date: 10/03/2006

Page: 4/6

Effects of Exposure

Inhalation: Harmful if inhaled. If hydrogen sulphide gas is liberated due to contact with acid, it may cause headache, nausea, dizziness, confusion, weakness, unconsciousness, convulsions, and death.

Eves: Causes eve burns.

Skin: Harmful if absorbed through skin. Causes skin irritation.

Ingestion: Harmful if swallowed. If free gastric acidity is high, hydrogen sulfide is liberated in the stomach and may cause systemic toxic effects such as vomiting, respiratory depression, tremors, convulsions and death.

Acute Toxicity Data:

Oral LD50 (rat): 1,600 mg/kg

Skin irritation: severe (The product may be absorbed through the skin.)

 Skin irritation: Corrosive (4-hour DOT Skin Corrosivity Test, Destruction of skin tissue as a result of more than 3 minutes exposure.)

• Eye irritation: severe

12. Ecological information

Environmental data is not available.

13. Disposal considerations

Discharge, treatment, or disposal may be subject to federal, state, commonwealth, provincial, or local laws. Since emptied containers retain product residue, follow label warnings even after container is emptied.

14. Transport information

The information given below is provided to assist in documentation. It may supplement the information on the package. The package in your possession may carry a different version of the label depending on the date of manufacture. Depending on inner packaging quantities and packaging instructions, it may be subject to specific regulatory exceptions. Please consult the product packaging for further details.

IATA: UN Number: UN3267

Proper shipping name: Corrosive liquid, basic, organic, n.o.s. (Potassium

polysulfides)

Class: 8 Packaging group: II

IMDG: UN Number: UN3267

Proper shipping name: CORROSIVE LIQUID, BASIC, ORGANIC, N.O.S.

(Potassium polysulfides)

Class: 8
Packaging group: II

US DOT: UN Number: UN3267

Revision Date: 08/23/2006 000000015369/Version: 2.0 Print Date: 10/03/2006

Page: 5/6

Proper shipping name: Corrosive liquid, basic, organic, n.o.s. (Potassium

polysulfides)

Class: 8 Packaging group: II

For more transportation information, go to: www.kodak.com/go/ship.

15. Regulatory information

U.S. California Prop. 65: none

Carcinogenicity Classification (components present at 0.1% or more):

International Agency for Research on Cancer (IARC): none

American Conference of Governmental Industrial Hygienists (ACGIH): none

U.S. National Toxicology Program (NTP): none

U.S. Occupational Safety and Health Administration (OSHA): none

Chemical(s) subject to the reporting requirements of U.S. Section 313 or Title III of the Superfund Amendments and Reauthorization Act (SARA) of 1986 and 40 CFR Part 372: none

16. Other information

The data below reflects current legislative requirements whereas the product in your possession may carry a different version of the label depending on the date of manufacture.

US/Canadian Label Statements:

CONTAINS: Potassium polysulfides (37199-66-9)

DANGER!

CONTACT WITH ACID LIBERATES FLAMMABLE AND POISONOUS GAS CAUSES SKIN AND EYE BURNS DUST, MIST OR VAPOUR IRRITATING TO THE EYES AND RESPIRATORY TRACT HARMFUL IF INHALED, ABSORBED THROUGH SKIN, OR SWALLOWED

Do not breathe vapours or spray mist.

Do not get in eyes and avoid contact with skin and clothing.

Keep container tightly closed.

Use only with adequate ventilation.

Wash thoroughly after handling.

FIRST AID: If inhaled, move to fresh air. Get medical attention. In case of contact, immediately flush eyes or skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes. Get medical attention immediately. Wash contaminated clothing before re-use. Destroy or thoroughly clean contaminated shoes. If swallowed, DO NOT induce vomiting. Never give anything by mouth to an unconscious person. Call a physician or poison control center immediately.

Notes to physician: Strong alkalis bind tissue protein. Following initial flushing of the eye with water, continued irrigation of the eye with saline is recommended. Treatment should be continued until pH of tears reaches neutral.

Revision Date: 08/23/2006 000000015369/Version: 2.0 Print Date: 10/03/2006

Page: 6/6

Keep out of reach of children.

Do not handle or use until safety precautions in Material Safety Data Sheet (MSDS) have been read and understood.

Since emptied containers retain product residue, follow label warnings even after container is emptied.

IN CASE OF FIRE: Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide.

IN CASE OF SPILL: Absorb spill with vermiculite or other inert material, then place in a container for chemical waste. Clean surface thoroughly to remove residual contamination.

The information contained herein is furnished without warranty of any kind. Users should consider these data only as a supplement to other information gathered by them and must make independent determinations of suitability and completeness of information from all sources to assure proper use and disposal of these materials and the safety and health of employees and customers and the protection of the environment. The information relating to the working solution is for guidance purposes only, and is based on correct mixing and use of the product according to instructions.

R-1, S-3, F-1, C-0